

Filed by Express Mail
(Receipt No. 4050492)
on February 13, 1999
pursuant to 37 C.F.R. 1.10.
by [Signature]

SPECIFICATION

TITLE OF THE INVENTION

This application is a continuation of international application
CDMA RECEIVER
BACKGROUND OF THE INVENTION *No. PCT/JP99/04990, filed*
September 14, 1999.

5 This invention relates to a CDMA receiver and, more particularly, to a CDMA receiver for applying despread processing to direct waves or delayed waves that arrive via each path of multiple paths, applying synchronous detection processing to the despread signals obtained,
10 combining the detection signals of respective paths and discriminating the received data on the basis of the combined signal.

DS-CDMA (Direct Sequence Code Division Multiple Access) communication is the focus of attention as a
15 promising candidate for next-generation wireless access because this scheme makes possible high-speed data communication for voice, facsimile, electronic mail, still images and moving images. Such a DS-CDMA communication scheme achieves spectrum spreading by
20 directly multiplying a signal (transmit information), which is to undergo spectrum spreading, by a signal (a spreading code) having a band much broader than that of the first-mentioned signal.

In mobile communication, maximum frequency is
25 decided by the velocity of the mobile station and the frequency of the carrier waves, random changes in amplitude and phase occur and so does fading. As a consequence, it is very difficult to achieve stable

K.
10/19/07

203120.6542007

reception at maximum frequency in comparison with stationary radio communication. The above-mentioned spread-spectrum communication scheme is effective as means for mitigating such deterioration caused by the influence of frequency-selective fading. The reason for this is that since a narrow-band signal is spread over a high-frequency band and then transmitted. This means that even if a decline in reception field strength occurs in a certain specific frequency region, information from elsewhere in the band can be reconstructed with little error.

Further, with mobile communication, delayed waves from distant high-rise buildings or mountains give rise to a multipath fading environment if fading similar to that mentioned above is produced by the receiver surroundings. In the case of direct sequence (DS), the delayed waves constitute interference with respect to the spreading code and invite a decline in reception characteristics. RAKE reception is known as one method in which such delayed waves are used positively in improvement of characteristics. RAKE reception involves subjecting each delayed wave that arrives via each path of multipath to despread processing using a code identical with the spreading code, subjecting the obtained despread signals to delay processing conforming to the path to thereby make the timings agree, subsequently performing synchronous detection, combining signals, which are obtained by such synchronous

10074939.021302

detection, upon applying weighting in accordance with the reception level, and discriminating data using the combined signal.

Fig. 28 is a diagram showing the structure of a
5 CDMA receiver. A radio unit 1 converts a high-frequency signal received by an antenna to a baseband signal by applying a frequency conversion (RF \rightarrow IF conversion). A quadrature detector 2 subjects the baseband signal to quadrature detection and outputs in-phase component (I-
10 phase component) data and quadrature component (Q-component) data. The quadrature detector 2 includes a receive-carrier generator 2a, a phase shifter 2b for shifting the phase of the receive carrier by $\pi/2$, and multipliers 2c, 2d for multiplying the baseband signal
15 by the receive carrier and outputting the I-component signal and the Q-component signal. Low-pass filters (LPF) 3a, 3b limit the bands of these output signals and AD converters 4a, 4b convert the I- and Q-component signals to digital signals and input the
20 digital signals to a searcher 5, which performs a multipath search, and to a RAKE receiver 6. The RAKE receiver 6 has a plurality of fingers 6a₁ to 6a_n for executing processing (despreading, delay-time adjustment, synchronous detection, etc) conforming to the respective
25 paths of multipath, a RAKE combiner 6b for weighting the signals, which are output from the fingers, in accordance with the reception level and then combining the signals, and a discrimination unit 6c for

202507493001

discriminating data using the combined signal.

The reception level of the signal component (the desired signal) of the local channel sent from a transmitter varies in dependence upon multipath, as shown in Fig. 29, and arrival time at the receiver differs as well. Further, the signal received at the antenna includes other channel components in addition to the channel that has been assigned to the local receiver. Accordingly, the searcher 5 extracts the desired signal from the antenna receive signal by a matched filter (not shown) using the spreading code of its own channel. That is, when a direct-sequence signal (DS signal) that has been influenced by multipath is input to the search 5, the latter performs an autocorrelation operation using the matched filter and outputs a pulse train having a plurality of peaks. The searcher detects multipath from the pulse train based upon peak signals MP_1 to MP_4 that are larger than a threshold value, detects delay times t_1 to t_4 on each of the paths and inputs despreading-start timing data and delay-time adjustment data to the fingers $6a_1$ to $6a_z$ corresponding to the respective paths.

A despreaders/delay-time adjusting unit 7 of each of the fingers $6a_1$ to $6a_z$ subjects a delayed wave that arrives via a prescribed path to despread processing using a code identical with the spreading code, performs dump integration, then applies delay processing conforming to the path and inputs the processed signal

10074939.024302

to a synchronous detector (phase correction unit) 8.
The synchronous detector 8 detects a pilot signal
contained in the receive signal, finds the phase
difference between this pilot signal and an already
5 known pilot signal, and restores the phase of the
despread information signal by the amount of the phase
difference. The information signal and pilot signal
contained in the receive signal both undergo phase
rotation owing to transmission. However, if a signal-
10 point position vector P_{ACT} (see Fig. 30) of this pilot
signal is known on the receiving side, then the phase-
rotation angle θ of the pilot signal ascribable to
transmission will be obtained because the ideal signal-
point position vector P_{IDL} is already known. Accordingly,
15 the synchronous detector 8 detects the pilot signal,
calculates the phase-rotation angle θ thereof and
subjects each information signal to processing to rotate
it by a rotation angle of $-\theta$, thereby restoring the
original information signal. As a result, the
20 discrimination unit 6c is capable of performing highly
precise demodulation of data.

The signals output from the phase detectors 8 of
respective ones of the fingers 61_a to $6a_z$ are combined
upon being weighted in accordance with the reception
25 level, and the discrimination unit 6c discriminates "1",
"0" of the data using the combined signal.

Fig. 31 is a diagram showing another structure of
the CDMA receiver, in which components identical with

10074939.021302

those of the CDMA receiver of Fig. 28 are designated by like reference characters. This structure differs in that (1) a valid-path detector 5a is provided within the searcher to detect whether a path is valid or invalid and input the result of the path valid/invalid detection to the RAKE combiner 6b, and (2) only output signals from fingers conforming to the valid paths are weight in accordance with the signal level and combined by the RAKE combiner 6b. Fig. 32 is a diagram showing the structure of the valid-path detector. Average power calculation units $5b_1$ to $5b_N$ calculate first to Nth average powers based upon the outputs of matched filters (not shown), and a power comparator 5c obtains maximum and minimum average powers P_{max} , P_{min} , recognizes valid paths that satisfy the following expressions:

$$P_{max} \geq P > (P_{max} - N)$$

$$P \geq P_{min} + M$$

and invalid paths that do not satisfy these expressions, and reports these paths to the RAKE combiner 6b.

With the RAKE receiver of Fig. 28, all paths are combined as valid paths by the RAKE combiner and data discrimination is performed based upon the combined signal. However, the paths include invalid paths and the invalid paths constitute interference. In other words, in accordance with the RAKE receiver of Fig. 28, even invalid signals are combined, a decline in sensitivity is produced and receiver performance is affected.

10074939.021302

On the other hand, with the RAKE receiver of Fig. 31, path validity/invalidity is detected and only valid paths are combined. As a result, sensitivity and performance are improved in comparison with the RAKE receiver of Fig. 28. It should be noted that a base station performs transmission power control in order to render reception power constant (in order to render reception quality at the base station constant). As a result, reception power of direct waves or delayed waves shown in (a) of Fig. 33 declines in accordance with transmission power control, as shown in (b) of Fig. 33, and therefore it becomes difficult to distinguish between valid paths and invalid paths. Further, since all paths are not necessarily valid paths (paths on which gain is obtained), characteristics deteriorate if all of these paths are combined. In other words, with a conventional RAKE receiver, there are instances where invalid paths are regarded as valid paths and combined and instances where valid paths are regarded as invalid paths and are not combined. A problem that results in a decline in sensitivity and performance.

Further, with the conventional RAKE receiver, a problem which arises is the need to provide the highly precise valid-path detector circuit, which relies upon the setting of two-stage threshold values, as mentioned above, in order to detect invalid paths without causing a decline in sensitivity.

Further, in a CDMA receiver, it is necessary to

10074939 021300

change the valid/invalid-path discrimination processing or parameters depending upon the transmission rate.

However, the conventional RAKE receiver does not possess such a function and, hence, cannot cope with

5 transmission rate.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide a CDMA receiver in which a decline in sensitivity due to invalid paths can be suppressed and
10 transmission power can be reported.

Another object of the present invention is to provide a CDMA receiver in which, with regard to paths for which the valid/invalid path determination cannot be made, the output of a finger is weighted in accordance
15 with the degree of valid-path likeness, a valid path is rescued and a path that has no valid-path likeness is excluded, whereby sensitivity and receiver performance are improved.

Another object of the present invention is to
20 provide a CDMA receiver for controlling a set level (breakpoint level), which is a criterion of degree of valid-path likeness, in accordance with a change of transmission rate, and weighting a finger output in accordance with the degree of valid-path likeness.

25 Another object of the present invention is to provide a CDMA receiver that does not require a highly precise valid-path detector circuit.

Another object of the present invention is to

10074939.021302
205720.6564001

provide a CDMA receiver in which sensitivity or receiver performance is improved by varying a set level, which is for discriminating a valid path, based upon a reference SIR or maximum/minimum value of transmission power when
5 the reference SIR of transmission power control is changed in order to make an error rate equal to a set value or when the maximum/minimum value of transmission power is changed.

The present invention relates to a CDMA receiver
10 for applying despread processing to direct wave or delayed waves that arrive via each path of multiple paths, applying synchronous detection processing to the despread signals obtained, combining the detection signals of respective paths and discriminating the
15 received data on the basis of the combined signal. In the CDMA receiver of the present invention, (1) a weighting unit provided for every path is so adapted that if a prescribed signal component (reception power, SIR, etc.) of a direct wave or delayed wave that arrives
20 via an assigned path is below a set level, the weighting unit applies weighting, which conforms to the level of this signal component, to an output signal (cf. the detection signal); (2) a RAKE combiner combines signals output from the weighting units of the respective paths;
25 and (3) a data discrimination unit discriminates receive data based upon the output signal of the combiner. In this case, the weighting is made M^{-N} (where M is an integer equal to or greater than 2), and the smaller the

10074939.024302

signal level becomes in comparison with a set level, the larger N is made.

Thus, with regard to a path for which the valid/invalid path determination cannot be made, weighting is applied to a finger output in accordance with the degree of valid path likeness, as a result of which valid paths can be rescued. Moreover, by reducing the weighting of paths that have no valid path likeness, invalid paths can be excluded. This makes it possible to improve sensitivity and receiver performance. Further, the lower the transmission rate of a symbol becomes and the greater the spreading gain, the lower the above-mentioned set level (breakpoint level) is made. If this arrangement is adopted, the set level (breakpoint level) serving as the criterion of degree of valid path likeness can be controlled in accordance with a change in transmission rate and weighting that conforms to the degree of valid path likeness can be added onto a finger output. Further, reception power can be calculated in approximate terms by multiplying the combined signal by the reciprocal of maximum weighting among the weightings of respective paths.

Further, when a set level for certifying a valid path is set based upon reception power in a CDMA receiver according to the present invention, a maximum level P_{max} or minimum level P_{min} of reception power of each path is detected, a value $(P_{max} - \Delta Y)$ obtained by subtracting a set level ΔY from the maximum level P_{max} ,

10074939.021302

or a value ($P_{min} + \Delta Z$) obtained by adding a set level ΔZ to the minimum level P_{min} , is adopted as the above-mentioned set level, a weighting coefficient is decided based upon the difference or ratio between the actual
5 reception level of each path and the set level, and the output signal is weighted. Alternatively, when a set level for certifying a valid path is set based upon a SIR, the SIR of each path is estimated, a weighting coefficient is decided based upon the difference or
10 ratio between the estimated SIR and the set SIR serving as the set level, and the output signal is weighted. In this case, when a reference SIR of transmission power control is updated in such a manner that an error rate becomes the set value, the set SIR also is updated. If
15 this arrangement is adopted, the sensitivity of a RAKE receiver and receiver performance can be improved.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is diagram showing the structure of a CDMA receiver according to the present invention;

20 Fig. 2 is a diagram showing the structure of a weighting processor for outputting a weighted channel estimation signal;

Fig. 3 is a diagram useful in describing a synchronous detection operation;

25 Fig. 4 shows characteristics of a relationship between input power and output power;

Fig. 5 is an fdTslot characteristic diagram;

Fig. 6 is a diagram showing the structure of a CDMA

10074939.021302

receiver composed of a plurality of branches;

Fig. 7 is a diagram showing the structure of a weighting processor for optimizing a breakpoint by spreading gain;

5 Fig. 8 is a diagram showing an arrangement for calculating reception power;

Fig. 9 is a diagram showing the structure of a phase compensation unit and weighting processor;

Fig. 10 is a flowchart of processing for deciding a weighted channel estimation signal;

Fig. 11 is an example of numerical values of various signals up to the decision of a weighted channel estimation signal;

Fig. 12 is a diagram showing another structure of a weighting processor;

Fig. 13 is a diagram showing yet another structure of a weighting processor;

Fig. 14 is a diagram useful in describing a running mean of Y slots of a channel estimation signal;

20 Fig. 15 is a diagram showing the structure of a finger in a case where weighting is performed after synchronous detection;

Fig. 16 is a first embodiment of the weighting processor of Fig. 15;

25 Fig. 17 is a second embodiment of the weighting processor of Fig. 15;

Fig. 18 is a third embodiment of the weighting processor of Fig. 15;

10074939.021302

Fig. 19 is a diagram showing the structure of a finger in a case where breakpoint is set by a SIR;

Fig. 20 is a flowchart of processing for deciding a weighted channel estimation signal using an estimated
5 SIR and a set SIR;

Fig. 21 is a diagram useful in describing SIR estimation;

Fig. 22 is a diagram showing the structure of a finger in a case where weighting is performed after
10 synchronous detection;

Fig. 23 shows an embodiment in which weighting processing is executed using a received information signal;

Fig. 24 is a flowchart of processing in a case
15 where weighting processing is executed using a received information signal;

Fig. 25 is a diagram showing the structure of a CDMA receiver of an embodiment in which a weighting coefficient is decided by a searcher;

Fig. 26 shows an embodiment for controlling a
20 breakpoint (in a case where the breakpoint is set based upon a SIR);

Fig. 27 shows an embodiment for controlling a
breakpoint (in a case where the breakpoint is set based
25 upon reception power);

Fig. 28 is a diagram showing the structure of a CDMA receiver according to the prior art;

Fig. 29 is a diagram useful in describing a delay

10074939.021302

profile;

Fig. 30 is a diagram useful in describing phase rotation of a pilot signal;

Fig. 31 is a diagram showing another structure of a CDMA receiver according to the prior art;

Fig. 32 is a diagram showing the structure of a valid-path detector; and

Fig. 33 is a diagram useful in describing a problem encountered in the prior art.

10

DESCRIPTION OF THE PREFERRED EMBODIMENT

(A) CDMA receiver

(a) Overall structure

Fig. 1 is a diagram showing the structure of a CDMA receiver according to the prior art. A radio unit 11 converts a high-frequency signal received by an antenna 10 to a baseband signal by applying a frequency conversion (RF \rightarrow IF conversion). A quadrature detector 12 subjects the baseband signal to quadrature detection and outputs in-phase component (I-component) data and quadrature component (Q-component) data. The quadrature detector 12 includes a receive-carrier generator 12a, a phase shifter 12b for shifting the phase of the receive carrier by $\pi/2$, and multipliers 12c, 12d for multiplying the baseband signal by the receive carrier and outputting the I-component signal and the Q-component signal. Low-pass filters (LPF) 13a, 13b limit the bands of these output signals, AGC circuits 14a, 14b control gain automatically in such a manner that the

10074939.021302

output level is rendered constant, and AD converters 15a, 15b convert the I- and Q-component signals to digital signals and input the digital signals to a searcher 16 and RAKE receiver 17. A reception power detector 18
5 measures reception power and inputs the measured power to the RAKE receiver 17.

The RAKE receiver 17 has a plurality fingers 17a₁ to 17a_z for executing processing (despreading, delay-time adjustment, synchronous detection, etc) conforming to
10 the respective paths of multipath, a RAKE combiner 17b for weighting the signals, which are output from the fingers, in accordance with the reception level and then combining (by maximal ratio combining) the signals, and a discrimination unit 17c for discriminating data using
15 the combined signal. Upon receiving input of a direct-sequence signal (DS signal) that has been influenced by the multipath effect, the searcher 16 detects multipath by performing an autocorrelation operation using a matched filter and inputs despreading-start timing data
20 and delay-time adjustment data of each path to the corresponding one of the fingers 17a₁ ~ 17a_z.

A despreader/delay-time adjusting unit 21 of each of the fingers 17a₁ to 17a_z subjects a direct wave or delayed wave that arrives via a prescribed path to
25 despread processing using a code identical with the spreading code, performs dump integration, then applies delay processing conforming to the path and outputs two types of signals, namely a pilot signal (reference

10074939.021302
20251220 16554200T

signal) and information signal. A phase compensator 22 averages the voltages of the I- and Q-components of the pilot signal over a prescribed number of slots and outputs channel estimation signals I_t , Q_t . One slot is
5 a basic unit for performing transmission power control and is composed of a plurality of symbols. This is an example in which one frame (10 ms) is equal to 16 slots.

A weighting processor 23 subjects the estimation channel signals (I_t, Q_t) at time t to weighting
10 processing and outputs weighted channel estimation signals. Fig. 2 is a diagram useful in describing weighting processing. A normalizing processor 23a applies normalization processing to the channel estimation signals (I_t, Q_t) input thereto. Normalization
15 processing refers to processing through which the channel estimation signals (I_t, Q_t) are made a circle of radius 1. Accordingly, the normalizing processor 23a obtains a multiple C that satisfies the following equation:

$$20 \quad C \cdot (I_t^2 + Q_t^2)^{1/2} = 1 \quad (1)$$

and obtains normalized channel estimation signals A_t , B_t ($A_t^2 + B_t^2 = 1$) in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t) \quad (2)$$

25 Here $(I_t^2 + Q_t^2)$ is the reception power. In other words, the normalizing processor 23a finds the multiple C for which reception power P will become 1, thereby normalizing the channel estimation signals. If

10074939.021302

reception power P increases, C decreases; if reception power P decreases, then C increases.

A weighting-coefficient setting processor 23b converts the multiple C to a 2^L format and executes
5 weighting processing in accordance with the L obtained by the conversion, channel estimation signals (A_t, B_t) and a separately set threshold value (referred to as a "breakpoint" below). For example, a value referred to as " m " is set in the weighting-coefficient setting
10 processor 23b as the breakpoint in advance. When the channel estimation values (I_t, Q_t) are input to the weighting processor 23 at time t , the normalizing processor 23a obtains (A_t, B_t) and the multiple C by normalization processing, converts C to the 2^L format
15 and inputs the result to the weighting-coefficient setting processor 23b. The latter compares L with the breakpoint m . This comparison processing is implemented by performing the operation $N = L - m$ and then discriminating the sign thereof. If the amplitudes of
20 the channel estimation signals (I_t, Q_t) are large, i.e., if the reception power P is high and $N \leq 0$ ($L \leq m$) holds, then weighted channel estimation signals (A_t', B_t') are output in accordance with the following equation:

$$(A_t', B_t') = (A_t/2^L, B_t/2^L) = (I_t, Q_t) \quad (3)$$

25 On the other hand, if the amplitudes of the channel estimation signals (I_t, Q_t) are small, i.e., if the reception power P is low and $N > 0$ ($L > m$) holds, then the weighted channel estimation signals (A_t', B_t') are output

10074939-021302

in accordance with the following equation:

$$(At', Bt') = (At/2^{L+N}, Bt/2^{L+N}) = (It/2^N, Qt/2^N) \quad (4)$$

The weighted channel estimation signals (At', Bt') are used at the time of synchronous detection and 2^{-N} becomes
5 the weighting coefficient.

A synchronous detector 24 performs synchronous ~~detection~~ in accordance with the following equation:

$$\begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} At & Bt \\ -Bt & At \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix} \quad (5)$$

using the weighted channel estimation signals (At', Bt') ,
10 as shown in Fig. 3. Originally, demodulation of the receive information signals (I, Q) is performed by applying phase-rotation processing to the receive information signals (I', Q') using normalized channel estimation signals (At, Bt) that have not been weighted.
15 According to the present invention, however, the channel estimation signals are weighted by $1/2^N$ and therefore a result multiplied by $1/2^N$ is obtained as the demodulated signals (I, Q) from the synchronous detector 24. Multipliers 25a, 25b thenceforth perform a weighted
20 squaring operation with regard to the I- and Q-components of the demodulated signal in order to implement RAKE combining. As a result, $(It^2/4^N, Qt^2/4^N)$ is obtained.

Thus, if $L \leq m$ holds, then reception power is high,
25 the corresponding path is considered to be a valid path (weighting coefficient = 1) and synchronous detection is performed using (It, Qt) as is. If $L > m$ holds, on the other hand, the reception power is low and whether the

2025074939-021302

corresponding path is a valid path or invalid path is unclear. Accordingly, synchronous detection is performed upon weighting (I_t, Q_t) by $1/2N$, which conforms to the difference N between L and m . As a result, with
5 regard to a path for which the valid/invalid path determination cannot be made, a finger output is weighted in accordance with the degree of valid path likeness. A valid path therefore can be rescued and, moreover, an invalid path can be excluded by reducing
10 the weighting of a path that has no valid path likeness. This makes it possible to improve sensitivity and receiver performance.

(b) Input/output characteristics of RAKE receiver

Fig. 4 shows the input/output characteristics of a
15 RAKE receiver according to the present invention. These are characteristics for a case where the baseband input after despreading has 10 bits and the breakpoint is at $m=4$. The horizontal and vertical axes represent input power and output power, respectively. This illustrates
20 a characteristic A for a case where the present invention is used (i.e., weighting is applied) and a characteristic B for a case where the present invention is not used (no weighting applied). Point a is the breakpoint. According to the present invention, the
25 above-described weighting operation is performed with respect to a receive signal below point a. This has the effect of rendering a certain signal more certain and rendering an uncertain signal more uncertain.

10074939.024302

(c) Weighting coefficient

A weighting coefficient is expressed above in a 2^{-N} format. This is advantageous in that a weighting coefficient can be obtained by a simple arrangement
5 involving only a bit shift in software processing and hardware implementation. If it is desired to carry out a more detailed setting of weighting coefficient, however, the weighting coefficient can be expressed by M^{-N} , where M represents a positive integer and N is a
10 real number. By adopting 3, 4, 5, ... as M, it is possible to obtain a steeper curve with respect to signals below the breakpoint, and the effect of maximal ratio combining is enhanced.

(d) fdTslot characteristic

15 Fig. 5 is an fdTslot characteristic diagram, in which the horizontal and vertical axes represents fdTslot (fading) and a requisite E_b/N_0 . A represents a characteristic for a case where weighting processing according to the invention is applied and B represents a
20 characteristic for a case where weighting processing according to the invention is not applied. Characteristic B in a characteristic that prevails when path timing is set from a searcher in order of decreasing reception level and all set paths are
25 combined by a RAKE receiver irrespective of whether a path is valid or invalid. By contrast, characteristic A is one that prevails when a breakpoint is set and a weighting coefficient M^{-N} is applied. By setting a

10074939.024302

breakpoint, weighting with regard to valid and invalid paths is carried out so that it is possible to obtain a characteristic improvement of X dB.

(e) Diversity structure

5 Fig. 1 illustrates the structure of a single branch. However, a multiple-branch structure (diversity structure) can be adopted and it is possible to adopt an arrangement in which the outputs from these branches are subjected to maximal ratio combining and data is
10 discriminated based upon the result of combination. Fig. 6 is a diagram showing the structure of a CDMA receiver composed of a plurality of branches. A CDMA receiver similar to that of Fig. 1 is provided for each branch, the outputs of these branches are subjected to maximal
15 ratio combining and data is discriminated. Each branch in Fig. 6 is identically constructed and components identical with those of Fig. 1 are designated by like reference characters. The CDMA receiver of each branch differs from that of Fig. 1 in that (1) the
20 searcher is eliminated; (2) reception power is measured from the output of the AD converter; (3) the RAKE combiner 17b combines the outputs of the fingers as is; and (4) a multiplier 17d is provided and multiplies reception power by combined signal. A maximal ratio
25 combiner 19 combines the outputs of the fingers at a ratio that conforms to the magnitude of reception power, and a discrimination unit 20 performs data discrimination based upon the output of the maximal

10074939.021302

ratio combiner.

(f) Optimization of breakpoint

In a CDMA receiver, it is necessary to set a breakpoint that conforms to spreading gain. In a case
5 where the spreading rate (chip frequency) is 4.096 MHz
and the symbol rates are 32 ksps, 64 ksps, 128 ksps, ...,
the spreading gains will be 21 dB, 18 dB, 15 dB,
The higher the spreading gain, the lower the reception
level at which a path is regarded as a valid path can be
10 made and the larger m can be made. Accordingly, as
shown in Fig. 7, if m represents the breakpoint at a
transmission rate of 32 ksps, then breakpoints are set
in correspondence with the symbol rates in a breakpoint
conversion table 23c. The breakpoint corresponding to
15 the actual symbol rate is read out of the breakpoint
conversion table 23c and is set in the weighting-
coefficient setting processor 23b.

Since a base station is capable of ascertaining the
spreading gain of each individual mobile station, the
20 base station can recognize that there are several
current symbol rates. Accordingly, if the current
transmission rate of the mobile station is 32 ksps,
weighting processing is executed using m as the
breakpoint. If the transmission rate of the mobile
25 station changes to 64 ksps, weighting processing is
executed using $(m+1)$ as the breakpoint.

(g) Calculation of reception power

In a case where RAKE combination is employed using

10074939.021302

the present invention, weighting is applied and therefore the correct reception power cannot be reported. However, by multiplying the signal after RAKE combination by the reciprocal of the weighting coefficient before combination, it is possible to calculate the value of reception power and a reported value of reception power can be generated. Fig. 8 is a diagram showing an arrangement for calculating reception power. Here the weighting coefficient of a first path is 0.5, that of a second path is 0.25, that of a (P-1)th path is 0.25, and that of a Pth path is 0.75. A weighting-coefficient comparator 26 compares the magnitudes of the weighting coefficients on the respective paths and obtains the largest weighting coefficient (0.75 in the Figure). A multiplier 27 multiplies the RAKE-combined data by the reciprocal (=1.33) of the largest weighting coefficient to obtain an approximate value of reception power. That is, by multiplying the combined signal by the reciprocal of the weighting coefficient for the path having the highest degree of certainty, an approximate value of reception power can be calculated in a simple manner.

(B) Weighting processor

(a) First embodiment of weighting processor

Fig. 9 is a diagram showing the structure of a first embodiment of the weighting processor 23 of Fig. 1. This sets a weighting coefficient using a pilot signal. The phase compensator 22 and weighting processor 23 are

10074939.021302

illustrated. Fig. 10 is a flowchart of processing for generating a weighted channel estimation signal.

The phase compensator 22 averages the voltages of the I- and Q-components of the pilot signal over one slot and outputs channel estimation signals (I_t , Q_t) (step 101). The normalizing processor 23a includes multipliers 31, 32 for performing the operations I_t^2 , Q_t^2 when the channel estimation signals (I_t , Q_t) are input thereto, an adder 33 adds I_t^2 and Q_t^2 , a multiple deciding unit 34 finds the multiple C that satisfies the following equation:

$$C^2 \cdot (I_t^2 + Q_t^2) = 1 \quad (1)'$$

and a normalization arithmetic unit 35 finds the normalized channel estimation signals A_t , B_t ($A_t^2 + B_t^2 = 1$) in accordance with Equation (2) (step 102).

Next, normalization arithmetic unit 35 converts C to the 2^L format and inputs A_t , B_t , L to the weighting-coefficient setting processor 23b (step 103). The weighting-coefficient setting processor 23b executes weighting processing using the entered L and channel estimation signals (A_t , B_t) as well as the separately set breakpoint m. Specifically, the weighting-coefficient setting processor 23b performs the operation $N = L - m$ and discriminates the sign of N (steps 104, 105). If $N \leq 0$ holds, i.e., if reception power is high, the weighting-coefficient setting processor 23b outputs the weighted channel estimation signals (A_t' , B_t') = (I_t , Q_t) in accordance with Equation (3) (step 106). If the

2025T20.6E64/001

reception power is low and $N > 0$ ($L > m$) holds, on the other hand, then the weighting-coefficient setting processor 23b outputs the weighted channel estimation signals $(At', Bt') = (It/2^N, Qt/2^N)$ in accordance with Equation (4) (step 107). The synchronous detector 24 performs synchronous detection using these weighted channel estimation signals (At', Bt') .

Fig. 11 is an example of actual numerical values in a case where the normalized channel estimation signals (At, Bt) , multiple $C (= 2^L)$, $N (= L-m)$ and weighted channel estimation signals (At', Bt') are found in accordance with the processing flowchart of Fig. 10 when $It = 0.0271$, $Qt = 0.0156$, $M = 2$, $m = 4$ hold.

(b) Second embodiment of weighted processor

Fig. 12 is a diagram showing the structure of a second embodiment of the weighting processor 23 of Fig. 1. In order to simplify the circuitry, this embodiment is such that the absolute values of the It and Qt components are calculated and the multiple C is decided in approximate fashion utilizing the average of the absolute values.

The phase compensator 22 averages the voltages of the I- and Q-components of the pilot signal over one slot and outputs channel estimation signals (It, Qt) , and absolute-value calculation units 36, 37 of the normalizing processor 23a calculate absolute values $|It|$, $|Qt|$ when the channel estimation signals (It, Qt) are input thereto. The adder 23 adds $|It|$ and $|Qt|$ and the

10074939, 021302

multiple deciding unit 34 finds the multiple C that satisfies the following equation:

$$C \cdot (|I_t| + |Q_t|) / 2 = 1 \quad (6)$$

That is, the multiple deciding unit 34 finds the
5 multiple C that makes the average of the absolute values equal to one. Next, the normalization arithmetic unit 35 finds the normalized channel estimation signals A_t , B_t in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

10 converts C to the 2^L format and inputs A , B_t , L to the weighting-coefficient setting processor 23b. By processing similar to that of the first embodiment, the weighting-coefficient setting processor 23b outputs the weighted channel estimation signals (A_t', B_t') .

15 (c) Third embodiment of weighting processor

Fig. 13 is a diagram showing the structure of a third embodiment of the weighting processor 23 of Fig. 1. In order to simplify the circuitry, this embodiment is such that the absolute values of the I_t and Q_t
20 components are calculated and the multiple C is decided in approximate fashion utilizing the larger of the absolute values.

The phase compensator 22 averages the voltages of the I- and Q-components of the pilot signal over one
25 slot and outputs channel estimation signals (I_t, Q_t) , and the absolute-value calculation units 36, 37 of the normalizing processor 23a calculate absolute values $|I_t|$, $|Q_t|$ when the channel estimation signals (I_t, Q_t) are

10074939.021302

$$5 \quad C \cdot C' = 1 \quad (7)$$

10 At, Bt in accordance with the following equation:

converts C to the 2^L format and inputs A, Bt, L to the weighting-coefficient setting processor 23b. By processing similar to that of the first embodiment, the weighting-coefficient setting processor 23b outputs the weighted channel estimation signals (A_t', B_t').

In the first to third embodiments of weighting processor 23, a voltage average of the pilot signal over one slot is output as the channel estimation signals (I_t, Q_t). However, the pilot signal can be averaged over a plurality of slots and the average can be adopted as the channel estimation signals (I_t, Q_t). Fig. 14 shows an example in which the average value not over one slot but over Y (1, 3, 5 ...) slots is adopted as the channel estimation signals (I_t, Q_t). The average value over a plurality of slots having symmetry with respect to the local slot is calculated and output.

(e) Other structure of weighting processor

The foregoing is for a case where the breakpoint is m , the multiple is $C (= 2^L)$, the operation $N = L - m$ is performed, weighting is made 1 if $N \leq 0$ holds and $1/2^N$ if $N > 0$ holds. In the first embodiment of the weighting processor, C is a multiple that satisfies the following equation:

$$C \cdot (I t^2 + Q t^2)^{1/2} = 1 \quad (1)$$

Since reception power $P = I t^2 + Q t^2$, C is a multiple that satisfies

$$C^2 \cdot P = 1$$

If P is found by substituting $C = 2^L$ into the above equation, we have

$$P = 1/4^L$$

Since $L = m$ is the breakpoint at the boundary of a valid path and invalid path, the breakpoint level of reception power becomes $1/4^m$. Accordingly, the weighting processor can be constructed in such a manner that if reception power P is greater than $1/4^m$, the path is a valid path and the weighting is made 1, and such that if $P < 1/4^m$ holds, the smaller the value of P , the smaller the weighting becomes.

More specifically, in general, a predetermined reception power P_m is set as the breakpoint level and the weighting processor 23 can be constructed in such a manner that if the actual reception power P is greater than the breakpoint level (set power) P_m , the weighting is made 1, and such that if $P < P_m$ holds, the smaller

the value of P, the smaller the weighting becomes.

(f) Other structure of weighting processor

It is also possible to construct the weighting processor 23 in such a manner that when the
5 predetermined reception power P_m is set as the breakpoint level, the weighting coefficient is decided based upon the ratio between the reception power P and breakpoint level P_m . Specifically, the weighting processor 23 finds the multiple C that satisfies
10 $P_m = C \cdot P$
finds the normalized channel estimation signals A_t , B_t in accordance with the following equation:
 $(A_t, B_t) = C(I_t, Q_t)$
and converts C to the 2^L format. If reception power P
15 increases, C decreases, and if reception power P decreases, C increases.
The weighting processor 23 executes weighting processing in accordance with L obtained by the 2^L conversion, the channel estimation signals (A_t, B_t) and
20 the separately set breakpoint m. That is, the weighting processor 23 first compares L and the breakpoint m. This comparison processing is executed by performing the operation $N = L - m$ and discriminating the sign thereof. If the reception power P is high and $N \leq 0$ ($L \leq m$) holds,
25 then the weighted channel estimation signals (A_t', B_t') are output in accordance with the following equation:

$$(A_t', B_t') = (A_t / 2^L, B_t / 2^L) = (I_t, Q_t)$$

On the other hand, if the reception power is low and $N > 0$

100-4939-021302

($L > m$) holds, then the weighted channel estimation signals (A_t', B_t') are output in accordance with the following equation:

$$(A_t', B_t') = (A_t/2^{L+N}, B_t/2^{L+N}) = (I_t/2^N, Q_t/2^N)$$

- 5 (C) Embodiment in case where weighting is performed after synchronous detection

In the embodiment set forth above, weighting is applied to channel estimation signals and weighted multiplication is carried out in the synchronous
10 detector. However, weighting can be applied by multiplying the output signal of the synchronous detector by a weighting coefficient.

(a) Overall construction

Fig. 15 is a diagram showing the structure of a
15 finger in a case where weighting is performed after synchronous detection. Only one path is illustrated. The despreader/delay-time adjusting unit 21 subjects a direct wave or delayed wave that arrives via a prescribed path to despread processing using a code
20 identical with the spreading code, performs dump integration, then applies delay processing conforming to the path and outputs two types of signals, namely a pilot signal (reference signal) and information signal. The phase compensator 22 averages the voltages of the I-
25 and Q-components of the pilot signal over a prescribed number of slots and outputs channel estimation signals I_t, Q_t .

The weighting processor 23 subjects the entered

10074939.021302

estimation channel signals (I_t, Q_t) to normalization processing and outputs normalized channel estimation signals (A_t, B_t) and the channel estimation signals (I_t, Q_t) prior to normalization to a selector 41.

- 5 Normalization processing is performed by a method similar to that of normalization processing described in conjunction with Fig. 1. Specifically, the weighting processor 23 obtains a multiple C that satisfies the following equation:

10
$$C \cdot (I_t^2 + Q_t^2)^{1/2} = 1$$

and obtains normalized channel estimation signals A_t, B_t ($A_t^2 + B_t^2 = 1$) in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

- 15 Further, the weighting processor 23 converts the multiple C to a 2^L format, decides a weighting coefficient M^{-N} in accordance with the L obtained by the conversion and a separately set breakpoint m , and outputs the weighting coefficient.

- 20 In accordance with a selection signal SEL , the selector 41 selects and outputs the normalized channel estimation signals (A_t, B_t) or the channel estimation signals (I_t, Q_t) prior to normalization. The synchronous detector 24 performs synchronous detection
- 25 in accordance with the following equation:

$$\begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} A_t & B_t \\ -B_t & A_t \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix} \quad (5)'$$

or the following equation:

10074939.021302

$$\begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} I_t & Q_t \\ -Q_t & I_t \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix} \quad (5)''$$

using the weighted channel estimation signals selected by the selector 41. In a case where the normalized channel estimation signals (At, Bt) are used in synchronous detection, these channel estimation signals (At, Bt) merely contain phase information. Accordingly, synchronous detection applies only phase-rotation processing to the information signal, and the output signal after synchronous detection becomes voltage information. In such case, if it is necessary to perform maximal ratio combining at a latter stage, it is required that a power converter 42 convert the voltage information to power information in accordance with the following equation:

$$P = I^2 + Q^2$$

On the other hand, if the channel estimation signals (It, Qt) prior to normalization are used in synchronous detection, the channel estimation signals (It, Qt) contain not only phase information but also amplitude information. When synchronous detection is performed, therefore, the amplitude of the channel estimation signals and the amplitude of the detected information signal are multiplied. As a result, a power-converted synchronous detection signal is output from the synchronous detector 24 and therefore the intervention of the power converter 42 is unnecessary. A signal selector 43 selects the output of the power converter 42

10074939.024302

5
10

15

(b) First embodiment of weighting processor

20

25

Multipliers 51a, 51b perform the operations It^2 , Qt^2 when the channel estimation signals (It , Qt) are input thereto, an adder 51c adds It^2 and Qt^2 , and a multiple

deciding unit 51d finds the multiple C that satisfies the following equation:

$$C^2 \cdot (I_t^2 + Q_t^2) = 1$$

Multipliers 51e, 51f calculate the normalized channel estimation signals A_t , B_t ($A_t^2 + B_t^2 = 1$) in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

and inputs these to the selector 41 together with the channel estimation signals (I_t , Q_t). A weighting setting unit 51g converts C to the ML format (e.g., $M=2$) and executes weighting processing using L and the separately set breakpoint m. Specifically, the weighting setting unit 51g performs the operation $N = L - m$ and discriminates the sign of N. If $N \leq 0$ ($L \leq m$) holds, the weighting setting unit 51g outputs M^0 ($= 1$) as the weighting coefficient; if $N > 0$ ($L > m$) holds, the weighting setting unit 51g outputs M^{-N} as the weighting coefficient.

(c) Second embodiment of weighting processor

Fig. 17 is a diagram showing the structure of a second embodiment of the weighting processor 23 of Fig. 15. In order to simplify the circuitry, this embodiment is such that the absolute values of the I_t and Q_t components are calculated and the multiple C is decided in approximate fashion utilizing the average of the absolute values.

The phase compensator 22 averages the voltages of the I- and Q-components of the pilot signal over Y slots

10074939.021302

and outputs channel estimation signals (I_t , Q_t).

Absolute-value calculation units 52a, 52b calculate absolute values $|I_t|$, $|Q_t|$ when the channel estimation signals (I_t , Q_t) are input thereto. An adder 52c adds
5 $|I_t|$ and $|Q_t|$ and a multiple deciding unit 52d finds the multiple C that satisfies the following equation:

$$C \cdot (|I_t| + |Q_t|) / 2 = 1$$

That is, the multiple deciding unit 52d finds the multiple C that makes the average of the absolute values
10 equal to one. Next, multipliers 52e, 52f calculate the normalized channel estimation signals A_t , B_t in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

and input the products to the selector 41 together with
15 the channel estimation signals (I_t , Q_t). A weighting setting unit 52g executes processing similar to that of the weighting setting unit 51g of the first embodiment, decides the weighting coefficient M^{-N} and outputs the same.

20 (c) Third embodiment of weighting processor

Fig. 18 is a diagram showing the structure of a third embodiment of the weighting processor 23 of Fig. 15. In order to simplify the circuitry, this embodiment is such that the absolute values of the I_t and Q_t
25 components are calculated and the multiple C is decided in approximate fashion utilizing the larger of the absolute values.

The phase compensator 22 averages the voltages of

10074939.021302

the I- and Q-components of the pilot signal over Y slots and outputs channel estimation signals (I_t , Q_t).

Absolute-value calculation units 53a, 53b calculate absolute values $|I_t|$, $|Q_t|$ when the channel estimation signals (I_t , Q_t) are input thereto. A multiple deciding unit 53c adopts the larger of the absolute values as C' and finds the multiple C that satisfies the following equation:

$$C \cdot C' = 1$$

Next, multipliers 53d, 53e calculate the normalized channel estimation signals A_t , B_t in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

and input the products to the selector 41 together with the channel estimation signals (I_t , Q_t). A weighting setting unit 53f executes processing similar to that of the weighting setting unit 51g of the first embodiment, decides the weighting coefficient M^{-N} and outputs the same.

(D) Embodiment in which breakpoint is set by SIR

(a) Structure and operation

Fig. 19 is a diagram showing the structure of a finger in a case where breakpoint is set by a SIR. This illustrates only the structure of one finger. Fig. 20 is a flowchart of processing for outputting a weighted channel estimation signal using a set SIR and an estimated SIR. A SIR value ST for obtaining an error rate 10^{-3} after error correction is set in advance.

10074939.021302

The despreader/delay-time adjusting unit 21 subjects a direct wave or delayed wave that arrives via a prescribed path to despread processing using a code identical with the spreading code, performs dump
5 integration, then applies delay processing conforming to the path and outputs two types of signals, namely a pilot signal and information signal. The phase compensator 22 averages the voltages of the I- and Q- components of the pilot signal over a prescribed number
10 of slots and outputs channel estimation signals I_t , Q_t . An SIR estimation unit 55 estimates an SIR (= S) by a method described below (step 201). A weighting processor 56 finds the multiple C that satisfies the following equation (step 202):

15 $S_t = C \cdot S$

finds the normalized channel estimation signals A_t , B_t in accordance with the following equation:

$$(A_t, B_t) = C(I_t, Q_t)$$

and converts C to the 2^L format (step 203). If the
20 estimated SIR increases, C decreases; if the estimated SIR decreases, C increases.

The weighting processor 56 executes weighting processing in accordance with the L obtained by the 2^L conversion, the channel estimation signals (A_t , B_t) and
25 the separately set threshold value (breakpoint) m. That is, the weighting processor 56 compares L with the breakpoint m. This comparison processing is implemented by performing the operation $N = L - m$ and then

2025074939.021302

discriminating the sign thereof (steps 204, 205). If the estimated SIR is large and $N \leq 0$ ($L \leq m$) holds, then weighted channel estimation signals (At', Bt') are output (step 206) in accordance with the following equation:

$$5 \quad (At', Bt') = (At/2^L, Bt/2^L) = (It, Qt)$$

If the estimated SIR is small and $N > 0$ ($L > m$) holds, then the weighted channel estimation signals (At', Bt') are output (step 207) in accordance with the following equation:

$$10 \quad (At', Bt') = (At/2^{L+N}, Bt/2^{L+N}) = (It/2^N, Qt/2^N)$$

The weighted channel estimation signals (At', Bt') are used at the time of synchronous detection and 2^{-N} becomes the weighting coefficient.

A synchronous detector 24 performs synchronous detection in accordance with the following equation:

$$15 \quad \begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} At & Bt \\ -Bt & At \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix} \quad (5)$$

using the weighted channel estimation signals (At', Bt') .

(b) Weighting coefficient.

Though the weighting coefficient is expressed above in a 2^{-N} format, the weighting coefficient can be expressed by M^{-N} , where M represents a positive integer and N is a real number. By adopting 3, 4, 5, ... as M , it is possible to obtain a steeper curve with respect to signals below the breakpoint, and the effect of maximal ratio combination is enhanced.

(c) Other structure of weighting processor

The foregoing is for a case where the breakpoint is m , the multiple is 2^L ($= C$), the operation $N = L - m$ is

10074939.021302

performed, weighting is made 1 if $N \leq 0$ holds and $1/2^N$ if $N > 0$ holds. Here C is a multiple that satisfies the following equation:

$$C \cdot S = S_T$$

- 5 Accordingly, if S is found by substituting $C = 2^L$ into the above equation, we have

$$S = S_T / 2^L$$

- Since $L = m$ is the breakpoint at the boundary of a valid path and invalid path, the breakpoint level of SCR becomes $S_T / 2^m$. Accordingly, the weighting processor 23 can be constructed in such a manner that if estimated SCR is greater than $S_T / 2^m$, the path is a valid path and the weighting is made 1, and such that if $S < S_T / 2^m$ holds, the smaller the value of estimated SIR, the smaller the weighting becomes.
- 10
15

- More specifically, in general, a predetermined SIR is set as the breakpoint level and the weighting processor 56 can be constructed in such a manner that if the actual estimated value SIR (= S) is greater than the set SIR, the weighting is made 1, and such that if estimated SIR is less than the set SIR, the smaller the estimated SIR, the smaller the weighting becomes.
- 20

(d) Method of calculated estimated SIR

- An example of SIR estimation in a case where the modulation scheme is QPSK and the number of pilot signals in one slot is four will now be described.
- 25

• Estimation of desired signal power (S)

Desired signal power (S) is calculated slot by slot

10074939.021302

in order to perform high-speed transmission power control. If we let the pilot of an Nth symbol in a certain slot be represented by $P_N(I_N, Q_N)$, the pilot signals in one slot will be $P_1(I_1, Q_1)$, $P_2(I_2, Q_2)$, $P_3(I_3, Q_3)$, $P_4(I_4, Q_4)$, as shown in Fig. 21, the voltages of these four symbols are added with regard to the in-phase components and quadrature components, and the averages of the summed voltages are obtained. Equation (8) below represents the average I_{ave} of the in-phase components, and Equation (9) below represents the average Q_{ave} of the quadrature components. Let the average reception point be $P_{ave} (I_{ave}, Q_{ave})$.

$$I_{ave} = (I_1 + I_2 + I_3 + I_4)/4 \quad (8)$$

$$Q_{ave} = (Q_1 + Q_2 + Q_3 + Q_4)/4 \quad (9)$$

The estimated power (S) of the desired signal is the power of the average reception point, namely

$$S = P_{ave}^2 = I_{ave}^2 + Q_{ave}^2 \quad (10)$$

•Estimation of interference power (I)

Interference power is represented by distance (variance) from a reference-signal point. The reference-signal point is $P_b ([P_{ave}^2/2]^{1/2}, [P_{ave}^2/2]^{1/2})$, and the in-phase and quadrature components become $1/\sqrt{2}$ of the average reception signal point P_{ave} . The deviation from the reference-signal point is the inference power of each symbol. If the average of one slot of the inference power is calculated and the average of a plurality of slots is obtained, this becomes the interference power I_p for calculating the estimated SIR.

10074939.021302

The following equation is an equation for calculating I_p .

$$I_p = \frac{1}{L} \sum_{j=1}^L \left[\frac{1}{N} \sum_{i=1}^N \left\{ \left(\frac{P_{ave}}{\sqrt{2}} - I_i \right)^2 + \left(\frac{P_{ave}}{\sqrt{2}} - Q_i \right)^2 \right\} \right] \quad (11)$$

L: average number of slots

N: average number of symbols

5 Thus if the estimated SIR is calculated, we have

$$SIR = S/I_p \quad (12)$$

(e) Embodiment in which weighting is performed
after synchronous detection

Fig. 22 is a diagram showing the structure of a
10 finger in a case where weighting is performed after
synchronous detection. Components identical with those
of the embodiment of Fig. 19 are designated by like
reference characters. This arrangement differs from
that of Fig. 19 in that (1) the synchronous detector 24
15 performs synchronous detection in accordance with the
following equation:

$$\begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} I_t & Q_t \\ -Q_t & I_t \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix} \quad (5)''$$

using the channel estimation signals (I_t , Q_t); (2) a
weighting coefficient decision unit 57 calculates the
20 weighting coefficient M^{-N} by a method the same as that of
Fig. 19 and inputs the coefficient to a weighting
processor 58; and (3) the weighting processor 58
multiplies the synchronous detection signal by the
weighting coefficient M^{-N} to applying weighting to the
25 finger output.

(E) Embodiment in case where weighting is
performed based upon reception power of
information signal

10074539.021302

Fig. 23 is a diagram showing the structure of a finger in a case where weighting is applied based upon the reception power of the information signal, and Fig. 24 is a flowchart of processing in a case where
5 weighting is applied based upon the reception power of the information signal.

The despreader/delay-time adjusting unit 21 subjects a direct wave or delayed wave that arrives via a prescribed path to despread processing using a code
10 identical with the spreading code, then applies delay processing conforming to the path and outputs two types of signals, namely a pilot signal and information signal (Idtn, Qdtn) (step 301). A channel estimation unit 61 generates channel estimation signals (It, Qt) by
15 averaging the entered pilot signals over one slot, applies normalization processing to the channel estimation signals (It, Qt) and inputs the normalized channel estimation signals (At, Bt) to the synchronous detector 24. That is, the channel estimation unit 61
20 finds the multiple C' that satisfies the following equation:

$$C' \cdot (It^2 + Qt^2)^{1/2} = 1$$

obtains normalized channel estimation signals (At, Bt) ($At^2 + Bt^2 = 1$) in accordance with the following
25 equation:

$$(At, Bt) = C' (It, Qt)$$

and inputs these to the synchronous detector 24 (step 302).

202520.68642001

The synchronous detector 24 performs synchronous detection in accordance with the following equation if the receive information signals (Idtn, Qdtn) are input thereto from the despreaders/delay-time adjusting unit 21

5 (step 303):

$$\begin{pmatrix} Idn \\ Qdn \end{pmatrix} = \begin{pmatrix} At & Bt \\ -Bt & At \end{pmatrix} \begin{pmatrix} Idtn \\ Qdtn \end{pmatrix}$$

An absolute-value calculation unit 62 calculates, symbol by symbol, the absolute values of the synchronously detected information signals, and an average calculation unit 63 obtains absolute-value averages Idave, Qdave over the number of symbols in one slot in accordance with the following equations (step 305):

$$\begin{aligned} Idave &= (|Id_1| + |Id_2| + \dots + |Id_n|)/n \\ Qdave &= (|Qd_1| + |Qd_2| + \dots + |Qd_n|)/n \end{aligned}$$

A weighting-coefficient setting processor 64 finds the multiple C that satisfies the following equation:

$$C \cdot (Idave^2 + Qdave^2)^{1/2} = 1$$

and executes normalization processing in accordance with the following equation (step 306):

$$(Idave', Qdave') = C \cdot (Idave, Qdave)$$

Further, the weighting-coefficient setting processor 64 converts C to the 2L format (step 307) and compares L with the breakpoint m. This comparison processing is executed by performing the operation $N = L - m$ (step 308) and discriminating the sign thereof (step 309). If $N \leq 0$ ($L \leq m$) holds, the weighting coefficient is 1. If $N > 0$ ($L > m$) holds, on the other hand, then the weighting

20250309 09:00

coefficient is 2^{-N} .

A delay element 65 delays the synchronous detection output (I_{dn} , Q_{dn}) for the amount of time it takes for the weighting coefficient to be found. A multiplier
5 outputs (I_{dn}' , Q_{dn}'), which is given by the following equation:

$$(I_{dn}', Q_{dn}') = (I_{dn}, Q_{dn})$$

to a RAKE combiner (step 310) if $N \leq 0$ ($L \leq m$) holds, and outputs (I_{dn}' , Q_{dn}'), which is given by the following
10 equation:

$$(I_{dn}', Q_{dn}') = (I_{dn}/2^N, Q_{dn}/2^N)$$

to the RAKE combiner (step 311) if $N > 0$ ($L > m$) holds.

(F) Embodiment in which weighting coefficient is decided in searcher

15 Fig. 25 is a diagram showing the structure of a CDMA receiver of an embodiment in which a weighting coefficient is decided by a searcher. Components identical with those shown in Fig. 1 are designated by like reference characters. This arrangement differs
20 from that of Fig. 1 in that (1) the weighting processor is deleted from the finger, with the weighting coefficient being decided by the searcher 16; (2) the synchronous detector 24 performs synchronous detection in accordance with the following equation:

$$\begin{pmatrix} I \\ Q \end{pmatrix} = \begin{pmatrix} I_t & Q_t \\ -Q_t & I_t \end{pmatrix} \begin{pmatrix} I' \\ Q' \end{pmatrix}$$

and (3) the maximal ratio combiner 17b multiplies the finger outputs by the weighting coefficients and combines the results.

10074939.021302

10074939.021302

A matched filter 16a in the searcher 16 calculates correlation values at respective ones of the timings and inputs these to average power detectors 16b₁ to 16b_n corresponding to respective ones of the timings. The

5 average power detectors 16b₁ to 16b_n perform amplitude addition with regard to the correlation values on a per-slot basis, thereby improving the S/N ratio, convert the amplitude averages of the slot to power and calculate the average power over a plurality of slots. On the

10 basis of this information, a path-timing detection and weighting coefficient setting unit 16c determines the timing of each path of multipath, compares the breakpoint and the average power value of the delayed path determined, and decides the weighting coefficient

15 M^{-N} for each path determined. The searcher 16 reports the weighting coefficient to the maximal ratio combiner 17b, and the latter discriminates "1", "0" of the data based upon the combined signal. It should be noted that the weighting coefficient is decided in accordance with

20 the method shown in Figs. 16 to 18.

(G) Control for changing over breakpoint

In transmission of information, transmission power control for controlling the transmission power of a mobile station is carried out by the base station in

25 such a manner that the minimum necessary error rate is obtained. Transmission power control of a high-speed closed loop for performing control in such a manner that estimated SIR will agree with the reference SIR is known

generally. Further, since the requisite E_b/I_o for obtaining the above-mentioned error rate varies depending upon an increase or decrease in subscribers and in dependence upon the propagation-path environment, etc., it is necessary to vary the reference SIR value in conformity therewith. For example, a graph requisite E_b/I_o based upon the propagation path is as shown in Fig. 5. Since the requisite E_b/I_o varies owing to fading, it is known that updating of the reference SIR value is required because of fading. In a case where updating of the SIR value is carried out, updating of the breakpoint also is performed at the same time.

Methods of updating the breakpoint include (1), a method of updating the set SIR in accordance with a change in reference SIR in a case where the breakpoint level is set by the SIR, and (2) a method of updating the breakpoint level based upon the maximum reception power or minimum reception power of the reception powers in each delayed path in a case where the breakpoint level is set by the reception power.

(a) Embodiment for case where breakpoint level is set by SIR

Fig. 26 shows an embodiment for controlling a breakpoint in accordance with a change in reference SIR in a case where the breakpoint is set based upon a SIR. Components identical with those of the structure shown in Fig. 19 are designated by like reference characters. A predetermined SIR value ($= S_T$) is set as the breakpoint

10074939.021302

level in the weighting processor 56. If the actual estimated SIR (= S) is greater than the set SIR (= S_T), the path is a valid path and the weighting processor adopts 1 as the weighting coefficient; if the estimated
5 SIR is less than the set SIR (= S_T), then the smaller the estimated SIR becomes, the smaller the weighting processor makes the weighting coefficient.

At the beginning, the reference SIR value needed to obtain the desired error rate and the breakpoint level
10 (the set SIR) S_T are set in a transmission power controller 71 and weighting processor 56, respectively. If transmission between the mobile station and base station starts under these conditions, an error-rate detector 72 detects an error rate e included in results
15 of discrimination from the discrimination unit 17c and compares the error rate e with a requisite error rate e_s . If $e > e_s$ holds, the error-rate detector 72 outputs a control signal for updating the reference SIR and the set SIR each by ΔX dB. As a result, a reference-SIR
20 updater 71a in the transmission power controller 71 updates the reference SIR in accordance with the following equation:

$$\text{reference SIR} + \Delta X \rightarrow \text{reference SIR}$$

Further, a breakpoint updating processor 73 also updates
25 the set SIR (= S_T) in accordance with the following equation:

$$S_T + \Delta X \rightarrow S_T$$

Changing ΔX dB may be performed in increments of Δn dB

20251220 16:54:00 10074939.021302

over a period of time, or ΔX dB may be updated a single time.

By virtue of the above operation, a change in propagation-point environment, etc. can be dealt with as
5 a relative breakpoint and not as an absolute breakpoint.

The weighting processor 56 estimates the actual SIR
(= S) and adopts 1 as the weighting coefficient if the
estimated SIR is greater than the set SIR (= S_T). If the
estimated SIR is less than the set SIR, then the
10 weighting processor 56 decides the weighting coefficient
C (= M^{-N}) in such a manner that the smaller the estimated
SIR becomes, the smaller the weighting coefficient
becomes, and calculates a weighted channel estimation
signal in accordance with the following equation:

15
$$(At', Bt') = C(It, Qt)$$

The synchronous detector 24 performs synchronous
detection using the weighted channel estimation signal.

(b) Embodiment for a case where breakpoint level
is set based upon reception power

20 Fig. 27 shows an embodiment of a RAKE receiver for
controlling breakpoint level based upon maximum power
among the reception power values of the respective
delayed paths in a case where the breakpoint level is
set based upon reception power. Components identical
25 with those of the structure shown in Fig. 1 are
designated by like reference characters.

At the beginning, the initial breakpoint level is
set in the weighting processor 23. If transmission

10074939.021302

between the mobile station and base station starts under these conditions, a reception power detector 81 provided in each of fingers 17a₁ to 17a₂ of the respective paths detects based upon $I_t^2 + Q_t^2$ the power of direct waves or delayed waves that arrive via the local path and inputs the detected power to a maximum-level detector 82. The latter detects the maximum reception power Pmax among the reception power values of all paths and inputs the same to a breakpoint updater 83. The latter executes updating of the breakpoint m in accordance with the following equation:

$$m = P_{\max} - \Delta Y$$

so that the difference between the maximum reception power Pmax and the breakpoint level will be ΔY dB at all times, and sets the new breakpoint level m in the weighting processor 23 of each finger. By virtue of the above operation, a change in propagation-point environment, etc. can be dealt with as a relative breakpoint and not as an absolute breakpoint.

The weighting processor 23 detects reception power and adopts 1 as the weighting coefficient if the reception power is above breakpoint level. If the reception power is below the breakpoint level, the weighting processor 23 decides the weighting coefficient $C (= M^{-N})$ in such a manner that the smaller the reception power becomes, the smaller the weighting coefficient becomes, and calculates a weighted channel estimation signal in accordance with the following equation:

2025-02-20 15:54:00

$$(A_t', B_t') = C(I_t, Q_t)$$

The synchronous detector 24 performs synchronous detection using the weighted channel estimation signal.

In the foregoing, the breakpoint level is
5 controlled by detecting the maximum power. However, it is also possible to control the breakpoint level by detecting minimum reception power P_{min} . That is, an arrangement can be adopted in which updating of the breakpoint m is performed in accordance with the
10 following equation:

$$m = P_{min} + \Delta Z$$

so that the difference between the minimum reception power P_{min} and the breakpoint level will be ΔZ dB at all times and the new breakpoint level m is set in the
15 weighting processor 23 of each finger.

Thus, in accordance with the present invention, the performance of a CDMA receiver can be improved.

10074939.021302